



DesignJet 750C Plus

Features:

- Crisp line drawings and near-photo-quality images
- Ideal for line drawings, layouts, illustrations, and presentations
- True 600-dpi black, 600-dpi-addressable color line drawings, and 300-dpi color images
- Prints 2- by 3-foot check plots in about 1.5 minutes, line drawings in about 4 minutes, and images in about 8 minutes
- Up to 16.7 million bold, brilliant colors and dense, dark black deliver presentation-quality output
- Accepts a wide variety of media to handle check plots, final output, presentations, overlays, and archiving
- HP JetDirect interface cards make network integration easy
- Queuing, nesting, roll feed and automatic cutter for efficient unattended printing
- Custom HP-developed drivers for AutoCAD® and Microsoft® Windows® take full advantage of printer features
- HP ZoomSmart scaling technology for large-format output from virtually any Windows application
- HP ColorSmart technology automatically optimizes output for vibrancy, clarity and balance
- 90-day warranty

Specs:

Print Technology:	Color or black-only thermal inkjet
Performance (2-3 ft):	Draft prints in about 1.5 minutes; final-quality, color lines in about 4 minutes; final-quality images in about 8 minutes
Maximum Resolution:	Black: 600-dpi; Color: Addressable 600-dpi (lines), 300-dpi (images)
Media Types:	Bond, coated and glossy papers and films, vellum, and clear and matte film for black and color; translucent bond for black-only
Media Sizes:	36-inch models Rolls: 36- and 24-in wide; Sheets: 8.3-in to 36-in wide 24-inch models Rolls: 24-in wide; Sheets: 8.3-in to 24-in wide Maximum length Rolls: 150 ft; Sheets 64 in
Margins:	Leading and trailing edges: 0.39-in for rolls; 0.67-in for sheets; Sides: 0.20-in
Media Handling:	Sheet and roll feed, automatic cutter, output bin
Memory:	Standard 8MB plus 3MB printing memory/Maximum: 72MB RAM
Languages:	HP-GL/2, HP-GL, HP RTL
Drivers:	Windows 95, 98, NT, 2000, XP

AutoCAD R12 - 2005

Interfaces, standard:	Ethernet, LocalTalk, IEEE-1284 compatible Centronics parallel, RS-232-C serial
Interfaces, optional:	HP JetDirect EX external network interface
Auto I/O Switching:	Yes
Warranty:	90 Days
WidthxDepthxHeight / Weight:	36-in models 54 inf. 27 inf. 47 in / 132 lb 24-in models 42 inf. 27 inf. 47 in / 108 lb
Shipping Dimensions / Weight:	36-in models 61 inf. 24 inf. 36 in / 219 lb 24-in models 50 inf. 24 inf. 36 in / 175 lb
Temperature:	Operating, Optimal 59° to 86° F; Storage -40° to 158° F
Operating Relative Humidity:	20% to 80%
Power Requirements:	Source 100-240 V AC ±10%; Frequency 50-60 Hz Power Consumption 140 watts maximum
Acoustics:	(Per ISO DP 7779 standard) Printing Idle Sound Pressure Level** 54 dB (A) <20 dB (A) Sound Power Level 6.5 Bels (A) <3.6 Bels (A)